

## 200 liter tank i Syrafast 316



**104,000,00 kr /st exkl moms**

item available on order

**Article type:** brand new mixing tank - type VC-SLA

**Additional information:** delivered with food certificate; *article price without agitator*; choice of 2 different types of agitators; see options; (The article can also be purchased without options);  $Ra < 0.8 \mu m$

**Volumetric volume (L):** 200 L

**Max. density P (kg/m<sup>3</sup>):** 1.200

**Ra inner weld:** 0,80

**Finish stainless steel:** 2b

**Pressure in tank:** ATM - atmosferic  
**Max. temperature (°C):** 80 °C  
**Min. temperature (°C):** -10 °C  
**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical  
**Configuration:** single-skin  
**Heat exchanger:** no  
**Insulation:** no  
**Mobile tank:** no

**Top type:** half hinging lid °  
**Shape of tank:** cylindrical  
**Bottom type:** conical 10 °  
**Total discharge:** yes  
**Fixation points:** 3 non adjustable feet

**Gasket manway(s):** EPDM  
**Valve:** RVS 316L  
**Fixation point(s):** RVS 304  
**Suitable for food industry:** yes  
**Documents included:** yes, optional

**Technical drawing included:** yes  
**Registration plate on the tank:** yes  
**Flange for agitator:** yes  
**CIP spray ball:** no, optional  
**Tank outlet:** inside Ø 40 mm

**Outlet type:** 11.850  
**Total outlet valve:** no, optional  
**Agitator:** no, optional  
**Agitator type:** propeller agitator  
**Position engine:** at the top

**Number of revolutions:** 1.500  
**Power:** 0,37  
**Voltage:** 400 V - three-phase  
**Agitator type 2:** propeller agitator

**Position engine:** at the top

**Number of revolutions:** 680

**Power:** 0,12

**Voltage:** 400 V - three-phase

**Top:** 3 mm

**Cylinder:** 3 mm

**Bottom:** 3 mm

**Internal diameter tank:** 670 mm

**Distance from outlet to ground:** 250 mm

**Outer diameter tank:** 676 mm

**Cylinder height:** 550 mm

**Total height of tank:** 1.118 mm

**Empty weight tank:** 70

**SKU:** 6251

## Mer information

## Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Nyttillverkad

Arbetstryck i tank: ATM – atmosferic

Finish rostfritt stål: 2b

Konfiguration: single-skin

Max. arbetstemperatur: 80 °C

Maximal densitet för produkten: 1200

Min. arbetstemperatur: -10 °C

Mobil tank: Nej

Övrig information: delivered with food certificate; article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);

Övrig information2: Ra=<0.8µm

Omrörare: Nej

Ra innersvets: 0,80

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical 10 °

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 200

## Utrustning

Fläns för omrörare: Ja

Märkskylt: Ja

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 40 mm

Teknisk ritning finns: Ja

Utloppstyp: 11.850

## Översikt material

Material: Syrafast 316

Fixeringspunkt(er): RVS 304



## Dimensioner av tank

Cylinderhöjd: 550 mm  
Invändig diameter: 670 mm  
Mått utlopp till marken: 250 mm  
Total höjd: 1.118 mm  
Ytterdiameter: 676 mm

## Omrörare

Kraft (kW): 0,37  
Position motor: at the top  
Typ av omrörare: propeller agitator  
Varvtal: 1.500  
Spänning (Volt): 400 V - three-phase

## Tjocklek på tank

Botten: 3 mm  
Cylinder: 3 mm  
Topp: 3 mm

## Mer

Isolerad: Nej  
Vikt: 70