

## 200 liter tank i Syrafast 316



**64,000,00 kr /st exkl moms**

item available on order

**Article type:** brand new mixing tank - type CBS-HLA

**Additional information:** flange for agitator is foreseen; *article price without agitator*; feel free to ask for agitation possibilities on this tank; Ra=<0.8µm

**Volumetric volume (L):** 200 L

**Max. density P (kg/m<sup>3</sup>):** 1.200

**Ra inner weld:** 0,80

**Finish stainless steel:** 2b

**Pressure in tank:** ATM - atmosferic  
**Max. temperature (°C):** 80 °C  
**Material wet parts:** SS AISI 316L (V4A)  
**Model:** vertical

**Configuration:** single jacketed with heat-exchanger  
**Heat exchanger:** yes  
**Insulation:** no  
**Mobile tank:** no  
**Top type:** conical 15 °

**Shape of tank:** cylindrical  
**Bottom type:** conical 15 °  
**Total discharge:** yes  
**Fixation points:** 3 adjustable feet  
**Legs:** Set of baseplates and adjusting pieces included

**Type of HE on the cylinder:** dimple-jacket  
**Height HE:** 375 mm  
**Number of sections:** 1  
**Water pressure HE:** 3 Bar  
**Contact surface cylinder:** 0,33 m<sup>2</sup>

**Connection HE:** 1"bsp male  
**Working temperature HE cylinder:** 80 °C  
**Heat exchanger:** RVS 304  
**Manway(s):** RVS 316  
**Gasket manway(s):** EPDM

**Valve:** RVS 316L  
**Fixation point(s):** RVS 304  
**Suitable for food industry:** yes  
**Documents included:** yes, optional  
**Technical drawing included:** yes

**Registration plate on the tank:** yes  
**Flange for agitator:** yes  
**Number of manways:** 1  
**Position of manway:** at the top



**Height manhole 1 (mm):** 400 mm

**CIP spray ball:** no, optional

**Tank outlet:** inside Ø 40 mm

**Outlet type:** DIN11851 male

**Total outlet valve:** no, optional

**Adjustable legs:** yes

**Agitator:** no, optional

**Top:** 3 mm

**Cylinder:** 3 mm

**Bottom:** 3 mm

**Distance from outlet to ground:** 250 mm

**Outer diameter tank:** 690 mm

**Cylinder height:** 500 mm

**Total height of tank:** 1.122 mm

**Empty weight tank:** 120

**SKU:** 9272

---

Mer information

## Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Nyttillverkad

Arbetstryck i tank: ATM – atmosferic

Finish rostfritt stål: 2b

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 80 °C

Maximal densitet för produkten: 1200

Mobil tank: Nej

Övrig information: flange for agitator is forseen; article price without agitator; feel free to ask for agitation possibilities on this tank; Ra=<0.8µm

Omrörare: Nej

Ra innersvets: 0,80

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical 15 °

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316L (V4A)

Volym i liter: 200

## Utrustning

Fläns för omrörare: Ja

Märkskylt: Ja

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 40 mm

Teknisk ritning finns: Ja

Utloppstyp: DIN11851 male

## Översikt material

Material: Syrafast 316

Fixeringspunkt(er): RVS 304

## Dimensioner av tank

Cylinderhöjd: 500 mm  
Mått utlopp till marken: 250 mm  
Total höjd: 1.122 mm  
Ytterdiameter: 690 mm

## Värmeväxlare

Anslutning värmeväxlare: 1" BSP male  
Arbetstemperatur värmeväxlare cylinder: 80 °C  
Höjd värmeväxlare: 375 mm  
Kontaktyta cylinder: 0,33 m<sup>2</sup>  
Typ av värmeväxlare på cylinder: dimple-jacket  
Vattentryck värmeväxlare: 3 Bar

## Tjocklek på tank

Botten: 3 mm  
Cylinder: 3 mm  
Topp: 3 mm

## Mer

Värmeväxlare: RVS 304  
Isolerad: Nej  
Vikt: 120