200 liter tank i Syrafast 316



64 000 SEK /st exkl moms

item available on order

Article type: brand new mixing tank - type CBS-HLA
Additional information: flange for agitator is forseen; *article price without agitator;* feel free to ask for agitation possibilities on this tank; Ra=<0.8µm
Volumetric volume (L): 200 L
Max. density P (kg/m³): 1.200
Ra inner weld: 0,80

Finish stainless steel: 2b
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. temperature (°C): 80 °C
Material wet parts: SS AISI 316L (V4A)
Model: vertical

Configuration: single jacketed with heat-exchanger
Heat exchanger: yes
Insulation: no
Mobile tank: no
Top type: conical 15 °

Shape of tank: cylindrical
Bottom type: conical 15 °
Total discharge: yes
Fixation points: 3 adjustable feet
Legs: Set of baseplates and adjusting pieces included

Type of HE on the cylinder: dimple-jacket
Height HE: 375 mm
Number of sections: 1
Water pressure HE: 3 Bar
Contact surface cylinder: 0,33 m²

Connection HE: 1"bsp male
Working temperature HE cylinder: 80 °C
Heat exchanger: RVS 304
Manway(s): RVS 316
Gasket manway(s): EPDM

Valve: RVS 316L
Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: yes, optional
Technical drawing included: yes

Registration plate on the tank: yes
Flange for agitator: yes
Number of manways: 1
Position of manway: at the top
Height manhole 1 (mm): 400 mm

CIP spray ball: no, optional
Tank outlet: inside Ø 40 mm
Outlet type: DIN11851 male
Total outlet valve: no, optional
Adjustable legs: yes

Agitator: no, optional
Top: 3 mm
Cylinder: 3 mm
Bottom: 3 mm
Distance from outlet to ground: 250 mm

Outer diameter tank: 690 mm
Cylinder height: 500 mm
Total height of tank: 1.122 mm
Empty weight tank: 120

SKU: 378020

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Nytillverkad
Arbetstryck i tank: ATM – atmospheric
Finish rostfritt stål: 2b
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 80 °C
Maximal densitet för produkten: 1200
Mobil tank: Nej
Övrig information: flange for agitator is forseen; article price without agitator; feel free to ask for agitation possibilities on this tank; Ra=<0.8µm
Omrörare: Nej
Ra innersvets: 0,80
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: conical 15 °
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316L (V4A)
Volym i liter: 200

Utrustning

Fläns för omrörare: Ja
Märkskylt: Ja
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 40 mm
Teknisk ritning finns: Ja
Utloppstyp: DIN11851 male

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): RVS 304

Dimensioner av tank

Cylinderhöjd: 500 mm
Mått utlopp till marken: 250 mm
Total höjd: 1.122 mm
Ytterdiameter: 690 mm

Värmeväxlare

Anslutning värmeväxlare: 1"BSP male
Arbetstemperatur värmeväxlare cylinder: 80 °C
Höjd värmeväxlare: 375 mm
Kontaktyta cylinder: 0,33 m²
Typ av värmeväxlare på cylinder: dimple-jacket
Vattentryck värmeväxlare: 3 Bar

Tjocklek på tank

Botten: 3 mm
Cylinder: 3 mm
Topp: 3 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Nej
Vikt: 120