

200 liter tank i Syrafast 316



42,000,00 kr /st exkl moms

Additional information: Tank hangs in a former stainless steel tilting frame (currently not tiltable); tank open at the top with a screwed-on, foldable stainless steel protective grille; outlet with plunger (requires on-site modification; plunger does not close tightly)

Volumetric volume (L): 200 L

Pressure in tank: ATM - atmosferic
Max. temperature (°C): 100 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single jacketed with heat-exchanger
Heat exchanger: yes
Insulation: no
Mobile tank: no

Top type: open
Total discharge: yes
Volume: 35 L
Max Overpressure: 4 Bar
Max. working temperature: 151 °C

Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Outlet of tank: DN50 DIN 11851
Agitator: yes
Number of revolutions: 1.450
Power: 2,20

Internal diameter tank: 740 mm
Outer diameter tank: 780 mm
Total height of tank: 1.850 mm

SKU: 483860

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: Tank hangs in a former stainless steel tilting frame (currently not tiltable); tank open at the top with a screwed-on, foldable stainless steel protective grille; outlet with plunger (requires

Övrig information2: on-site modification; plunger does not close tightly); we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 200

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 740 mm

Total höjd: 1.850 mm

Ytterdiameter: 780 mm

Omrörare

Kraft (kW): 2,20

Varvtal: 1.450

Mer

Isolerad: Nej