

200 liter tank i Syrafast 316



128 000 SEK /st exkl moms

Additional information: Diameter handhole appr. 200 mm; Metallic discolouration inside

Volumetric volume (L): 200 L

Pressure in tank: pressure

Max. pressure (Bar): 3,50 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 36 L

Max Overpressure: 2 Bar

Max. working temperature: 90 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 22

Agitator: yes

Number of revolutions: 840

Power: 0,25

Internal diameter tank: 590 mm

Outer diameter tank: 740 mm

Cylinder height: 600 mm

Total height of tank: 1.650 mm

SKU: 277381

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Diameter handhole appr. 200 mm; Metallic discolouration inside; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,50 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 200

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 600 mm
Invändig diameter: 590 mm
Total höjd: 1.650 mm
Ytterdiameter: 740 mm

Omrörare

Kraft (kW): 0,25
Varvtal: 840

Mer

Värmeväxlare: RVS 304
Isolerad: Ja