2000 liter tank i Rostfritt 304



41 000 SEK /st exkl moms

Article type: second-hand storage tank
Volumetric volume (L): 2.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: single jacketed with heat-exchanger
Heat exchanger: yes
Insulation: no
Mobile tank: no
Top type: dished

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Shape of tank: cylindrical
Bottom type: dished
Bottom outlet: yes
Total discharge: yes
Fixation points: 3 non adjustable feet

Type of HE on the cylinder: dimple-jacket
Position HE: the middle part of the cilinder
Water pressure HE: 2 Bar
Manway(s): RVS 304
Gasket manway(s): unknown

Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no

Flange for agitator: no
Number of manways: 1
Position of manway: cylinder
Height manhole 1 (mm): 430 mm x H 330 mm
Tank outlet: inside Ø

Outlet of tank: DN40
Agitator: no
Distance from outlet to ground: 160 mm
Outer diameter tank: 1.210 mm
Cylinder height: 2.100 mm

Total height of tank: 2.600 mm
Empty weight tank: 700

SKU: 487683

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single jacketed with heat-exchanger
Mobil tank: Nej
Omrörare: Nej
Tankens form: cylindrical
Total urtappning: Ja
Typ av botten: dished
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 2000

Utrustning

Dokument finns: Nei, det er det ikke.
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304

Dimensioner av tank

Cylinderhöjd: 2.100 mm
Mått utlopp till marken: 160 mm
Total höjd: 2.600 mm
Ytterdiameter: 1.210 mm

Värmeväxlare

Position värmeväxlare: the middle part of the cilinder
Typ av värmeväxlare på cylinder: dimple-jacket
Vattentryck värmeväxlare: 2 Bar

Mer

Isolerad: Nej
Vikt: 700

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se