2000 liter tank i Rostfritt 304



314 000 SEK /st exkl moms

Volumetric volume (L): 20.000 L
Pressure in tank: pressure
Max. temperature (°C): 80 °C
Material wet parts: SS AISI 304 (V2A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Volume: 34 L
Max Overpressure: 3 Bar
Max. working temperature: 95 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: cylinder

Outlet of tank: flange DN65
Agitator: yes
Top: 2,50 mm
Cylinder: 3 mm
Bottom: 4 mm

Internal diameter tank: 2.392 mm
Cylinder height: 4.470 mm
Total height of tank: 6.235 mm
Empty weight tank: 3.000

SKU: 567539

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 80 °C
Mobil tank: Nej
Övrig information: Food; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 20000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 4.470 mm
Invändig diameter: 2.392 mm
Total höjd: 6.235 mm

Tjocklek på tank
Botten: 4 mm
Cylinder: 3 mm
Topp: 2,50 mm

Mer
Isolerad: Ja
Vikt: 3.000