

2000 liter tank i Syrafast 316



230 000 SEK /st exkl moms

Additional information: Food; Manhole diameter approx. 410 mm

Volumetric volume (L): 2.000 L

Pressure in tank: vacuum

Max. pressure (Bar): 4 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 170 L

Max Overpressure: 5 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: available

Agitator: yes

Power: 5,50

Cylinder: 6 mm

Bottom: 8 mm

Internal diameter tank: 1.400 mm

Outer diameter tank: 1.540 mm

Cylinder height: 1.200 mm

Total height of tank: 3.250 mm

SKU: 566723

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Food; Manhole diameter approx. 410 mm; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 4 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 1.200 mm
Invändig diameter: 1.400 mm
Total höjd: 3.250 mm
Ytterdiameter: 1.540 mm

Omrörare

Kraft (kW): 5,50

Tjocklek på tank

Botten: 8 mm
Cylinder: 6 mm

Mer

Isolerad: Ja