2000 liter tank i Syrafast 316



231 000 SEK /st exkl moms

Additional information: Food; Manhole diameter approx. 410 mm
Volumetric volume (L): 2.000 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 4 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 170 L
Max Overpressure: 5 Bar

Max. working temperature: 150 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: available
Agitator: yes

Power: 5,50
Cylinder: 6 mm
Bottom: 8 mm
Internal diameter tank: 1.400 mm
Outer diameter tank: 1.540 mm

Cylinder height: 1.200 mm
Total height of tank: 3.250 mm

SKU: 566723

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 150 °C
Mobil tank: Nej
Övrig information: Food; Manhole diameter approx. 410 mm; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Omrörare: Ja
Övertryck: 4 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 2000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 1.200 mm
Invändig diameter: 1.400 mm
Total höjd: 3.250 mm
Ytterdiameter: 1.540 mm

Omrörare
Kraft (kW): 5,50

Tjocklek på tank
Botten: 8 mm
Cylinder: 6 mm

Mer
Isolerad: Ja