

2000 liter tank i Syrafast 316



166 000 SEK /st exkl moms

Additional information: Manhole 330 x 440 mm; Documentation manual available

Volumetric volume (L): 2.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Max Overpressure: 3 Bar

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 80

Agitator: yes

Internal diameter tank: 1.050 mm

Outer diameter tank: 1.150 mm

Cylinder height: 2.450 mm

Total height of tank: 3.550 mm

SKU: 276598

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: Manhole 330 x 440 mm; Documentation manual available; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 2.450 mm

Invändig diameter: 1.050 mm

Total höjd: 3.550 mm

Ytterdiameter: 1.150 mm

Mer

Värmeväxlare: RVS 304

Isolerad: Ja

