

20000 liter tank i Rostfritt 304



229,000,00 kr /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 20.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes
Fixation points: 4 adjustable feet

Insulation material: rockwool
Outer jacket (ornamental wall): RVS 304
Manway(s): RVS 304
Gasket manway(s): unknown
Fixation point(s): RVS 304

Suitable for food industry: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no

Number of manways: 1
Height manhole 1 (mm): 420 mm
Tank outlet: inside Ø 80 mm
Total outlet valve: no
Agitator: yes

Agitator type: tripad
Position engine: at the top
Number of revolutions: 31 / 62
Power: 3,30
Voltage: three-phase

Insulation body: yes
Insulation bottom/sides: yes
finish of the outer jacket: welded
Insulation thickness: 60
Internal diameter tank: 2.860 mm

Distance from outlet to ground: 500 mm
Outer diameter tank: 2.980 mm
Cylinder height: 3.200 mm
Total height of tank: 5.900 mm

Empty weight tank: 1.950

SKU: 20916

Mer information
