

20000 liter tank i Rostfritt 304



145 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 20.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no



Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 3 adjustable feet

Manway(s): RVS 304

Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 500 mm

Tank outlet: inside Ø 100 mm

Outlet type: DIN11850

Total outlet valve: no

Agitator: yes

Top: 3 mm

Cylinder: 3 mm

Bottom: 4 mm

Distance from outlet to ground: 460 mm

Outer diameter tank: 2.800 mm

Cylinder height: 3.000 mm

Total height of tank: 5.000 mm

Empty weight tank: 1.200

SKU: 59211

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 20000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 100 mm

Teknisk ritning finns: Nej

Utloppstyp: DIN11850

Utloppsventil: Nej

Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304

Material vätskeberörd del på omrörare: SS AISI 304 (V2A)

Dimensioner av tank

Cylinderhöjd: 3.000 mm

Mått utlopp till marken: 460 mm

Total höjd: 5.000 mm

Ytterdiameter: 2.800 mm

Tjocklek på tank

Botten: 4 mm

Cylinder: 3 mm

Topp: 3 mm

Mer

Isolerad: Nej

Vikt: 1.200