

20000 liter tank i Rostfritt 304



200 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 20.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Bottom outlet: yes

Total discharge: yes

Fixation points: 3 adjustable feet

Manway(s): RVS 304

Gasket manway(s): unknown

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Hinged lid: yes

Tank outlet: inside Ø 50 mm

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Power: 1,20

Voltage: 400 V - three-phase

Current: 4,20

Distance from outlet to ground: 500 mm

Outer diameter tank: 3.260 mm

Cylinder height: 2.535 mm

Total height of tank: 4.450 mm

Empty weight tank: 1.950

SKU: 294877

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Vertikal
Nyttillverkad/Begagnad: Begagnad
Arbetsstryck i tank: ATM – atmosferic
Konfiguration: insulated
Mobil tank: Nej
Övrig information: we can't give any guarantees about the agitator
Omrörare: Ja
Tankens form: cylindrical
Total urtappning: Ja
Typ av botten: conical
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 20000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304



Dimensioner av tank

Cylinderhöjd: 2.535 mm

Mått utlopp till marken: 500 mm

Total höjd: 4.450 mm

Ytterdiameter: 3.260 mm

Omrörare

Kraft (kW): 1,20

Position motor: at the top

Typ av omrörare: propeller agitator

Spänning (Volt): 400 V – three-phase

Mer

Isolerad: Ja

Vikt: 1.950