

## 20000 liter tank i Rostfritt 304



**199 000 SEK /st exkl moms**

**Article type:** second-hand mixing tank

**Additional information:** we can't give any guarantees about the agitator

**Volumetric volume (L):** 20.000 L

**Pressure in tank:** ATM - atmosferic

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** insulated

**Heat exchanger:** no

**Insulation:** yes



**Mobile tank:** no

**Top type:** conical

**Shape of tank:** cylindrical

**Bottom type:** conical

**Bottom outlet:** yes

**Total discharge:** yes

**Fixation points:** 3 adjustable feet

**Manway(s):** RVS 304

**Gasket manway(s):** unknown

**Fixation point(s):** RVS 304

**Suitable for food industry:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** no

**Flange for agitator:** no

**Number of manways:** 1

**Position of manway:** at the top

**Hinged lid:** yes

**Tank outlet:** inside Ø 50 mm

**Agitator:** yes

**Agitator type:** propeller agitator

**Position engine:** at the top

**Power:** 1,70

**Voltage:** 380 V - three-phase

**Current:** 3,70

**Distance from outlet to ground:** 500 mm

**Outer diameter tank:** 3.400 mm

**Cylinder height:** 2.535 mm

**Total height of tank:** 4.450 mm

**Empty weight tank:** 1.950

**SKU:** 294832

## Mer information

### Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 20000

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 50 mm

Teknisk ritning finns: Nej

### Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304



## **Dimensioner av tank**

Cylinderhöjd: 2.535 mm

Mått utlopp till marken: 500 mm

Total höjd: 4.450 mm

Ytterdiameter: 3.400 mm

## **Omrörare**

Kraft (kW): 1,70

Position motor: at the top

Typ av omrörare: propeller agitator

Spänning (Volt): 380 V – three-phase

## **Mer**

Isolerad: Ja

Vikt: 1.950