

20000 liter tank i Rostfritt 304



223,000,00 kr /st exkl moms

Article type: second-hand storage tank

Additional information: The covering around the insulation has come loose at the front, please look carefully at the photos.; we can't give any guarantees about the heating/cooling jacket

Volumetric volume (L): 20.000 L

Pressure in tank: pressure

Design pressure (Bar): 4,50 Bar

Max. pressure (Bar): 3,50 Bar

Material wet parts: SS AISI 304 (V2A)

Model: vertical



Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: dished

Bottom outlet: yes

Total discharge: yes

Fixation points: 3 adjustable feet

Type HE: spiral pipes inside the tank

Heat exchanger: RVS - 304 with rockwool insulation

Insulation material: PUR

Outer jacket (ornamental wall): RVS 304L

Manway(s): RVS 304

Gasket manway(s): unknown

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: cylinder

Height manhole 1 (mm): 320 mm x H 430 mm

Tank outlet: inside Ø 65 mm

Agitator: no

finish of the outer jacket: riveted

Distance from outlet to ground: 200 mm

Outer diameter tank: 3.000 mm

Cylinder height: 3.500 mm

Total height of tank: 4.900 mm

Empty weight tank: 3.000

SKU: 439067

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure

Designtryck för tanken: 4,50 Bar

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: The covering around the insulation has come loose at the front, please look carefully at the photos.; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 3,50 Bar

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: dished

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 20000



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 65 mm
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304
Isoleringsmaterial: PUR
Ytterbeklädnad: RVS 304L

Dimensioner av tank

Cylinderhöjd: 3.500 mm
Mått utlopp till marken: 200 mm
Total höjd: 4.900 mm
Ytterdiameter: 3.000 mm

Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: riveted
Isoleringsmaterial: PUR

Mer

Värmeväxlare: RVS - 304 with rockwool insulation
Isolerad: Ja
Vikt: 3.000