

20000 liter tank i Rostfritt 304 (dubbelmantlad)



231,000,00 kr /st exkl moms

Additional information: Chemistry; Tank with safety jacket, Fe (according to DIN 6616D); test overpressure tank 2 bar; test overpressure safety jacket: 0.6 bar; 2 loose bearing saddles, Fe; 1 manhole diameter 600 mm and 1 manhole diameter 500 mm; Tank without bottom outlet; bright protective coating outside; manhole cover plated

Volumetric volume (L): 20.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: horizontal

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: no

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside

Outlet of tank: non-existent
Internal diameter tank: 2.500 mm
Total height of tank: 2.950 mm
Total outer length: 4.700 mm

SKU: 419780

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Horisontell

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: Chemistry; Tank with safety jacket, Fe (according to DIN 6616D); test overpressure tank 2 bar; test overpressure safety jacket: 0.6 bar; 2 loose bearing saddles, Fe; 1 manhole diameter 600 mm and 1

Övrig information2: manhole diameter 500 mm; Tank without bottom outlet; bright protective coating outside ; manhole cover plated

Omrörare: Nej

Total urtappning: Nej

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 20000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Invändig diameter: 2.500 mm

Total höjd: 2.950 mm

Mer

Isolerad: Nej

