20000 liter tank i Rostfritt 304 (dubbelmantlad)



206 000 SEK /st exkl moms

Additional information: Vessel with safety double jacket made of Fe (to DIN 6616D); test overpressure vessel 2 bar; test overpressure safety double jacket: 0.6 bar; 2 loose bearing saddles, Fe; 1 manhole diameter 600 mm and 1 manhole diameter 500 mm; vessel without bottom outlet; light-colored protective coating on the outside; manhole cover plated
Volumetric volume (L): 20.000 L

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: horizontal

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: no

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside

Outlet of tank: non-existent
Internal diameter tank: 2.500 mm
Total height of tank: 2.950 mm
Total outer length: 4.700 mm

SKU: 419780

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Horisontell
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single-skin
Mobil tank: Nej
Övrig information: Chemistry; Tank with safety jacket, Fe (according to DIN 6616D); test overpressure tank 2 bar; test overpressure safety jacket: 0.6 bar; 2 loose bearing saddles, Fe; 1 manhole diameter 600 mm and 1
Övrig information2: manhole diameter 500 mm; Tank without bottom outlet; bright protective coating outside ; manhole cover plated
Omrörare: Nej
Total urtappning: Nej
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 20000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Invändig diameter: 2.500 mm
Total höjd: 2.950 mm

Mer

Isolerad: Nej