

2050 liter tank i Rostfritt 304



93 000 SEK /st exkl moms

Additional information: Heating coil in the cylinder at the bottom; manhole diameter 500 mm; insulating jacket with minor dents, paint partially detached; vessel bolted to Fe carriage (carriage with corrosion); build-up inside the vessel

Volumetric volume (L): 2.050 L

Pressure in tank: vacuum

Max. pressure (Bar): 4 Bar

Min. pressure (Bar): 0,80 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 304 (V2A)

Model: horizontal

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 14 L

Max Overpressure: 6 Bar

Max. working temperature: 200 °C

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 55

Internal diameter tank: 1.180 mm

Outer diameter tank: 1.370 mm

Total height of tank: 2.350 mm

Total outer length: 3.650 mm

SKU: 295325

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Horisontell

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Heating coil on the cylinder below; manhole diameter 500 mm; Insulation jacket with smaller dents, paintwork has partially come off; tank bolted to trolley made of Fe (trolley with signs of

Övrig information2: corrosion); Adhesions inside the tank; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 4 Bar

Total urtappning: Ja

Undertryck (vakuum): 0,80 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 2050

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Invändig diameter: 1.180 mm

Total höjd: 2.350 mm

Ytterdiameter: 1.370 mm

Mer

Värmeväxlare: RVS 304

Isolerad: Ja