

## 2068 liter tank i Syrafast 316



**259,000,00 kr /st exkl moms**

**Additional information:** pharmacy; outlet fitting incomplete; ; some residues of previous content

**Volumetric volume (L):** 2.068 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 3 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 150 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 160 L

**Max Overpressure:** 4 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 150 °C

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** 44

**Cylinder:** 4 mm

**Internal diameter tank:** 1.284 mm

**Outer diameter tank:** 1.550 mm

**Cylinder height:** 1.200 mm

**Total height of tank:** 2.550 mm

**SKU:** 304065

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: pharmacy; outlet fitting incomplete;; some residues of previous content; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2068

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316



## **Dimensioner av tank**

Cylinderhöjd: 1.200 mm  
Invändig diameter: 1.284 mm  
Total höjd: 2.550 mm  
Ytterdiameter: 1.550 mm

## **Tjocklek på tank**

Cylinder: 4 mm

## **Mer**

Isolerad: Ja