2100 liter tank i Rostfritt 304



178 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: Tank AD-2000 Merkblatt, agitator CE0344 ATEX Ex 2 1/3 G bc T4 ; hardly ever used; we can't give any guarantees about the agitator
Volumetric volume (L): 2.100 L
Max. density P (kg/m³): 1.400
Pressure in tank: pressure

Max. pressure (Bar): 0,50 Bar
Max. temperature (°C): 90 °C
Material wet parts: SS AISI 304 (V2A)
Model: vertical

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes
Insulation: no
Mobile tank: no
Top type: dished
Shape of tank: cylindrical

Bottom type: dished
Total discharge: yes
Fixation points: 3 supports for platform
Position HE: the complet cilinder
Water pressure HE: 2 Bar

Steam pressure HE: 0,50 Bar
Working temperature HE cylinder: 100 °C
Heat exchanger: RVS 304
Fixation point(s): RVS 304
Wet parts agitator(s): SS AISI 304L (V2A)

Suitable for food industry: no
Documents included: yes, optional
Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: no

Tank outlet: inside Ø 50 mm
Agitator: yes
Agitator type: propeller agitator
Position engine: at the top
Number of revolutions: 250

Power: 7,50
Voltage: 400 V - three-phase
Top: 5 mm
Cylinder: 7 mm
Bottom: 4 mm

Outer diameter tank: 1.560 mm
Cylinder height: 1.250 mm

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Total height of tank: 1.950 mm
Empty weight tank: 960

SKU: 417893

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 90 °C
Maximal densitet för produkten: 1400
Mobil tank: Nej
Övrig information: Tank AD-2000 Merkblatt, agitator CE0344 ATEX Ex 2 1/3 G bc T4 ; hardly ever used; we can't give any guarantees about the agitator
Omrörare: Ja
Övertryck: 0,50 Bar
Tankens form: cylindrical
Total urtappning: Ja
Typ av botten: dished
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 2100

Utrustning
Fläns för omrörare: Nej
Märkskylt: Ja
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Ja

Översikt material
Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Material vätskeberörd del på omrörare: SS AISI 304L (V2A)

Dimensioner av tank
Cylinderhöjd: 1.250 mm
Total höjd: 1.950 mm
Ytterdiameter: 1.560 mm

Värmeväxlare
Ångtryck värmeväxlare: 0,50 Bar
Arbetstemperatur värmeväxlare cylinder: 100 °C
Position värmeväxlare: the complet cilinder
Vattentryck värmeväxlare: 2 Bar

Omrörare
Kraft (kW): 7,50
Position motor: at the top
Typ av omrörare: propeller agitator
Varvtal: 250
Spänning (Volt): 400 V – three-phase

Tjocklek på tank
Botten: 4 mm
Cylinder: 7 mm
Topp: 5 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Nej
Vikt: 960