

2100 liter tank i Rostfritt 304



58 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: The manway cover is also available.; we can't give any guarantees about the agitator

Volumetric volume (L): 2.100 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no



Insulation: yes

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Bottom outlet: yes

Total discharge: yes

Fixation points: 3 non adjustable feet

Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304L

Manway(s): RVS 304

Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: headside

Height manhole 1 (mm): 450 mm

Tank outlet: inside Ø 50 mm

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Number of revolutions: 450

Voltage: 400 V - three-phase

Current: 3,15

Top: 3 mm

Cylinder: 3 mm

Bottom: 3 mm

Internal diameter tank: 1.200 mm

Distance from outlet to ground: 520 mm



Outer diameter tank: 1.320 mm

Cylinder height: 1.800 mm

Total height of tank: 3.400 mm

Empty weight tank: 500

SKU: 703640

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: The manway cover is also available.; we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 2100



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Isoleringsmaterial: Rockwool
Material vätskeberörd del på omrörare: SS AISI 304 (V2A)
Ytterbeklädnad: RVS 304L

Dimensioner av tank

Cylinderhöjd: 1.800 mm
Invändig diameter: 1.200 mm
Mått utlopp till marken: 520 mm
Total höjd: 3.400 mm
Ytterdiameter: 1.320 mm

Omrörare

Position motor: at the top
Typ av omrörare: propeller agitator
Varvtal: 450
Spänning (Volt): 400 V – three-phase

Tjocklek på tank

Botten: 3 mm
Cylinder: 3 mm
Topp: 3 mm



Tjocklek på ytterbeklädnad och isolering

Isoleringsmaterial: Rockwool

Mer

Isolerad: Ja

Vikt: 500