

2130 liter tank i Syrafast 316



112 000 SEK /st exkl moms

Additional information: pharmacy; Total height incl. foot pedestals and motor cover; double outlet pipe diameter inside approx. 35 mm; insulated jacket with slight damage; 1 crack in the upper double jacket connection

Volumetric volume (L): 2.130 L

Pressure in tank: vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 140 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 400 L

Max Overpressure: 4 Bar

Max. working temperature: 140 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: available

Agitator: yes

Number of revolutions: 201

Power: 4

Internal diameter tank: 1.260 mm

Outer diameter tank: 1.500 mm

Total height of tank: 4.050 mm

SKU: 270814

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 140 °C

Mobil tank: Nej

Övrig information: pharmacy; Total height including foot pedestals and engine cladding; Double outlet diameter tube inside approx. 35 mm; Insulation jacket with slight damage; 1 crack in the upper double jacket

Övrig information2: connection; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2130

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Invändig diameter: 1.260 mm

Total höjd: 4.050 mm

Ytterdiameter: 1.500 mm

Omrörare

Kraft (kW): 4

Varvtal: 201

Mer

Isolerad: Ja