2130 liter tank i Syrafast 316



113 000 SEK /st exkl moms

Additional information: pharmacy; Total height incl. foot pedestals and motor cover; double outlet pipe diameter inside approx. 35 mm; insulated jacket with slight damage; 1 crack in the upper double jacket connection
Volumetric volume (L): 2.130 L
Pressure in tank: pressure and vacuum

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. pressure (Bar): 3 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 140 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 400 L
Max Overpressure: 4 Bar

Max. working temperature: 140 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: available
Agitator: yes

Number of revolutions: 201
Power: 4
Internal diameter tank: 1.260 mm
Outer diameter tank: 1.500 mm
Total height of tank: 4.050 mm

SKU: 394964

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: isolert med varmeveksler
Max. arbetstemperatur: 140 °C
Mobil tank: Nej
Övrig information: pharmacy; Total height including foot pedestals and engine cladding; Double outlet diameter tube inside approx. 35 mm; Insulation jacket with slight damage; 1 crack in the upper double jacket
Övrig information2: connection; we can’t give any guarantees about the heating/cooling jacket; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 2130

Utrustning

Dokument finns: Nei, det er det ikke.
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Invändig diameter: 1.260 mm
Total höjd: 4.050 mm
Ytterdiameter: 1.500 mm

Omrörare
Kraft (kW): 4
Varvtal: 201

Mer
Isolerad: Ja