21500 liter tank i Syrafast 316



243 000 SEK /st exkl moms

Additional information: Manhole approx. 500 x 400 mm; total height listed includes railing; slight metallic discoloration on the inside
Volumetric volume (L): 21.500 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: 200

Top: 3 mm
Cylinder: 3 mm
Bottom: 6 mm
Internal diameter tank: 2.400 mm
Outer diameter tank: 2.560 mm

Cylinder height: 4.500 mm
Total height of tank: 9.000 mm

SKU: 703214

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated
Mobil tank: Nej
Övrig information: Manhole diameter: approx. 500 x 400 mm; dimensions as shown in the drawing
Omrörare: Nej
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 21500

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 4.500 mm
Invändig diameter: 2.400 mm
Total höjd: 7.839 mm
Ytterdiameter: 2.560 mm

Tjocklek på tank

Botten: 6 mm
Cylinder: 3 mm
Topp: 3 mm

Mer
Isolerad: Ja