21600 liter tank i Syrafast 316



204 000 SEK /st exkl moms

Additional information: Solvents; Manufactured according to DIN6618; piping inside the vessels; stand frame made of 1.4301 (stainless steel 304); manhole cover made of 1.4541 (stainless steel 304)
Volumetric volume (L): 21.600 L
Pressure in tank: vacuum
Max. pressure (Bar): 0,50 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 0,10 Bar

Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no

Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Position of manway: headside
Outlet of tank: flange DN50
Cylinder: 3,50 mm
Bottom: 5 mm

Internal diameter tank: 2.890 mm
Cylinder height: 2.500 mm
Total height of tank: 4.600 mm
Empty weight tank: 1.550

SKU: 413411

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single-skin
Mobil tank: Nej
Övrig information: Solvents; Built according to DIN6618; pipelines inside the tanks; stand frame, 1.4301 (Aisi 304); manhole cover, 1.4541 (Aisi 304)
Omrörare: Nej
Övertryck: 0,50 Bar
Total urtappning: Ja
Undertryck (vakuum): 0,10 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 21600

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 2.500 mm
Invändig diameter: 2.890 mm
Total höjd: 4.600 mm

Tjocklek på tank
Botten: 5 mm
Cylinder: 3,50 mm

Mer
Isolerad: Nej
Vikt: 1.550