

2171 liter tank i Syrafast 316



133 000 SEK /st exkl moms

Additional information: Confectionery industry; Outlet 1 block flange diameter pipe inside 80 mm with flanged, tapering fitting; slight metallic discoloration inside the tank; dents at the insulation jacket

Volumetric volume (L): 2.171 L

Pressure in tank: ATM - atmospheric



Max. temperature (°C): 100 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 158 L

Max Overpressure: 2,50 Bar

Max. working temperature: 90 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: available

Agitator: yes

Number of revolutions: 14

Power: 2,20

Internal diameter tank: 1.880 mm

Outer diameter tank: 2.090 mm

Cylinder height: 510 mm

Total height of tank: 2.100 mm

SKU: 277960

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: Confectionery industry; Outlet 1 block flange diameter pipe inside 80 mm with flanged, tapering fitting; slight metallic discoloration inside the tank; dents at the insulation jacket; we can't give

Övrig information2: any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2171

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 510 mm
Invändig diameter: 1.880 mm
Total höjd: 2.100 mm
Ytterdiameter: 2.090 mm

Omrörare

Kraft (kW): 2,20
Varvtal: 14

Mer

Värmeväxlare: RVS 304
Isolerad: Ja