22000 liter tank i Rostfritt 304



210 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: we can't give any guarantees about the agitator
Volumetric volume (L): 22.000 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 85 °C

Material wet parts: SS AISI 304 (V2A)
Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes

Mobile tank: no

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes

Fixation points: 3 adjustable feet
Insulation material: rockwool
Outer jacket (ornamental wall): RVS 304
Manway(s): RVS 304
Gasket manway(s): unknown

Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no

Flange for agitator: no
Number of manways: 2
Position of manway: cylinder
Height manhole 1 (mm): 420 mm x H 305 mm
Position 2nd manway: at the top

Height manhole 2 (mm): 420
Tank outlet: inside Ø 80 mm
Total outlet valve: no
Agitator: yes
Agitator type: propeller agitator

Position engine: in the cylinder
Number of revolutions: 69 / 142
Power: 2,20
Voltage: three-phase
Insulation body: yes

Insulation bottom/sides: yes
finish of the outer jacket: welded
Insulation thickness: 50
Internal diameter tank: 2.900 mm

Distance from outlet to ground: 600 mm

Outer diameter tank: 3.000 mm
Cylinder height: 3.550 mm
Total height of tank: 5.100 mm
Empty weight tank: 1.500

SKU: 381695

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: insulated
Max. arbetstemperatur: 85 °C
Mobil tank: Nej
Övrig information: we can't give any guarantees about the agitator
Omrörare: Ja
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: conical
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 22000

Utrustning
Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 80 mm
Teknisk ritning finns: Nej
Utloppsventil: Nej

Översikt material
Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Isoleringsmaterial: Rockwool
Ytterbeklädnad: RVS 304

Dimensioner av tank
Cylinderhöjd: 3.550 mm
Invändig diameter: 2.900 mm
Mått utlopp till marken: 600 mm
Total höjd: 5.100 mm
Ytterdiameter: 3.000 mm

Omrörare
Kraft (kW): 2,20
Position motor: in the cylinder
Typ av omrörare: propeller agitator
Varvtal: 69 / 142
Spänning (Volt): three-phase

Tjocklek på ytterbeklädnad och isolering
Finish utvändig mantel: welded
Isolering botten/gavlar: Ja
Isolering mantel: Ja
Isoleringsmaterial: Rockwool

Mer

Isoleringstjocklek OW: 50
Isolerad: Ja
Vikt: 1.500