

22000 liter tank i Rostfritt 304



148 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: Small dent in the decorative casing, take a good look at the last photo

Volumetric volume (L): 22.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 6 adjustable feet

Insulation material: rockwool

Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 304

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 400 mm

Tank outlet: inside Ø 80 mm

Total outlet valve: no

Agitator: no, optional

finish of the outer jacket: welded

Internal diameter tank: 2.650 mm

Distance from outlet to ground: 400 mm

Outer diameter tank: 2.800 mm

Cylinder height: 3.900 mm

Total height of tank: 5.200 mm

Empty weight tank: 1.500

SKU: 26415

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: Small dent in the decorative casing, take a good look at the last photo

Omrörare: Nej

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 22000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 80 mm

Teknisk ritning finns: Nej

Utloppsventil: Nej

Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304

Isoleringsmaterial: Rockwool

Ytterbeklädnad: RVS 304

Dimensioner av tank

Cylinderhöjd: 3.900 mm

Invändig diameter: 2.650 mm

Mått utlopp till marken: 400 mm

Total höjd: 5.200 mm

Ytterdiameter: 2.800 mm

Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: welded

Isoleringsmaterial: Rockwool

Mer

Isolerad: Ja

Vikt: 1.500