

22000 liter tank i Rostfritt 304



220,000,00 kr /st exkl moms

Article type: second-hand storage tank

Additional information: we can't give any guarantees about the heating/cooling jacket

Volumetric volume (L): 22.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 6 adjustable feet

Type of HE on the cylinder: heating/cooling jacket

Position HE: the lower part of the cylinder

Water pressure HE: 1 Bar

Type of HE on the bottom: heating/cooling jacket

Heat exchanger bottom connected with cylinder: yes

Connection of the bottom to the cylinder: binned isolation

Water pressure HE: 1 Bar

Insulation material: Rockwool

Manway(s): RVS 304

Gasket manway(s): unknown

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 420 mm

Hinged lid: yes

Tank outlet: inside Ø 80 mm

Agitator: no

Internal diameter tank: 2.700 mm

Distance from outlet to ground: 400 mm

Outer diameter tank: 2.800 mm

Cylinder height: 3.850 mm

Total height of tank: 5.150 mm

Empty weight tank: 2.100

SKU: 287834

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 22000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 80 mm

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304

Isoleringsmaterial: Rockwool

Dimensioner av tank

Cylinderhöjd: 3.850 mm

Invändig diameter: 2.700 mm

Mått utlopp till marken: 400 mm

Total höjd: 5.150 mm

Ytterdiameter: 2.800 mm

Värmeväxlare

Position värmeväxlare: the lower part of the cilinder

Typ av värmeväxlare på cylinder: heating/cooling jacket

Typ av värmeväxlare på botten: heating/cooling jacket

Vattentryck värmeväxlare: 1 Bar

Vattentryck värmeväxlare botten: 1 Bar

Tjocklek på ytterbeklädnad och isolering

Isoleringsmaterial: Rockwool

Mer

Isolerad: Ja

Vikt: 2.100