

2210 liter tank i Rostfritt 304



67 000 SEK /st exkl moms

Additional information: Food industry; 4 stainless steel 304 claws; manhole diameter approx. 420 mm; insulation only around the cylinder; the two vessels were placed in a stainless steel frame by the previous operator; this frame is still available and can be supplied at extra cost on request (see photos)

Volumetric volume (L): 2.210 L

Pressure in tank: ATM - atmosferic
Max. temperature (°C): 90 °C
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Position of manway: headside
Outlet of tank: flange DN65
Agitator: yes
Number of revolutions: 39
Power: 1,50

Internal diameter tank: 1.290 mm
Outer diameter tank: 1.420 mm
Cylinder height: 1.450 mm
Total height of tank: 2.550 mm

SKU: 303635

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated

Max. arbetstemperatur: 90 °C

Mobil tank: Nej

Övrig information: Food industry; 4 support brackets, Aisi 304; Manhole diameter approx. 420 mm; Insulation around the cylinder only; The previous operator had the two tanks in a stainless steel frame; This frame is

Övrig information2: still available and can be included upon request for an additional charge (see photos); we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 2210

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.450 mm

Invändig diameter: 1.290 mm

Total höjd: 2.550 mm

Ytterdiameter: 1.420 mm

Omrörare

Kraft (kW): 1,50

Varvtal: 39

Mer

Isolerad: Ja