

2245 liter tank i Syrafast 316



113,000,00 kr /st exkl moms

Additional information: 1 electric plug-in heater (4 kW) inside the tank; height-adjustable screws of the feet are no longer available; slight metallic discoloration inside the tank

Volumetric volume (L): 2.245 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 145 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 38

Bottom: 6 mm

Internal diameter tank: 1.250 mm

Outer diameter tank: 1.400 mm

Cylinder height: 1.500 mm

Total height of tank: 2.550 mm

SKU: 300184

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 145 °C

Mobil tank: Nej

Övrig information: 1 electric plug-in heater (4 kW) inside the tank; height-adjustable screws of the feet are no longer available; slight metallic discoloration inside the tank; we can't give any guarantees about the

Övrig information2: heating/cooling jacket

Omrörare: Nej

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2245

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.500 mm

Invändig diameter: 1.250 mm

Total höjd: 2.550 mm

Ytterdiameter: 1.400 mm

Tjocklek på tank

Botten: 6 mm

Mer

Isolerad: Ja