2245 liter tank i Syrafast 316



113 000 SEK /st exkl moms

Additional information: 1 electric plug-in heater (4 kW) inside the vessel; height-adjustable dome screws of the feet are no longer present; slight metallic discoloration inside the vessel
Volumetric volume (L): 2.245 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 145 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: 38
Bottom: 6 mm

Internal diameter tank: 1.250 mm
Outer diameter tank: 1.400 mm
Cylinder height: 1.500 mm
Total height of tank: 2.550 mm

SKU: 422111

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 145 °C
Mobil tank: Nej
Övrig information: 1 electric plug-in heater (4 kW) inside the tank; height-adjustable screws of the feet are no longer available; slight metallic discoloration inside the tank; we can’t give any guarantees about the
Övrig information2: heating/cooling jacket
Omrörare: Nej
Övertryck: 3 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 2245

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.500 mm
Invändig diameter: 1.250 mm
Total höjd: 2.550 mm
Ytterdiameter: 1.400 mm

Tjocklek på tank
Botten: 6 mm

Mer
Isolerad: Ja