

225 liter tank i Syrafast 316



132,000,00 kr /st exkl moms

Additional information: Chemistry; 4-legged frame, Aisi 304; Hand hole diameter approx. 155 mm; some residues of previous content

Volumetric volume (L): 225 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 1 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 95 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 60 L

Max Overpressure: 4 Bar

Max. working temperature: 95 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 25

Agitator: yes

Number of revolutions: 156 - 838

Power: 0,75

Internal diameter tank: 590 mm

Outer diameter tank: 800 mm

Total height of tank: 2.400 mm

SKU: 308413

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 95 °C

Mobil tank: Nej

Övrig information: Chemistry; 4-legged frame, Aisi 304; Hand hole diameter approx. 155 mm; some residues of previous content; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees

Övrig information2: about the agitator

Omrörare: Ja

Övertryck: 1 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 225

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 590 mm

Total höjd: 2.400 mm

Ytterdiameter: 800 mm

Omrörare

Kraft (kW): 0,75

Varvtal: 156 – 838

Mer

Isolerad: Ja