

2263 liter tank i Rostfritt 304



118,000,00 kr /st exkl moms

Volumetric volume (L): 2.263 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 80 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 26 L

Max Overpressure: 2 Bar

Max. working temperature: 80 °C

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: yes

Position of manway: in the bottom

Outlet of tank: DN50 DIN 11851

Top: 2,50 mm

Cylinder: 3 mm

Bottom: 3 mm

Internal diameter tank: 1.433 mm

Outer diameter tank: 1.439 mm

Cylinder height: 1.250 mm

Total height of tank: 2.230 mm

SKU: 272608

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nyttillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 80 °C
Mobil tank: Nej
Omrörare: Nej
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 2263

Utrustning

Dokument finns: Nej
Fläns för omrörare: Ja
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 1.250 mm
Invändig diameter: 1.433 mm
Total höjd: 2.230 mm
Ytterdiameter: 1.439 mm



Tjocklek på tank

Botten: 3 mm

Cylinder: 3 mm

Topp: 2,50 mm

Mer

Värmeväxlare: RVS 304

Isolerad: Nej