

## 2263 liter tank i Rostfritt 304



**118 000 SEK /st exkl moms**

**Volumetric volume (L):** 2.263 L

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 80 °C

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 26 L

**Max Overpressure:** 2 Bar

**Max. working temperature:** 80 °C

**Heat exchanger:** RVS 304

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** yes

**Position of manway:** in the bottom

**Outlet of tank:** DN50 DIN 11851

**Top:** 2,50 mm

**Cylinder:** 3 mm

**Bottom:** 3 mm

**Internal diameter tank:** 1.433 mm

**Outer diameter tank:** 1.439 mm

**Cylinder height:** 1.250 mm

**Total height of tank:** 2.230 mm

**SKU:** 272608

## Mer information

### Beskrivning av produkt

Material: Rostfritt 304  
Modell: Vertikal  
Nyttillverkad/Begagnad: Begagnad  
Arbetstryck i tank: ATM – atmosferic  
Konfiguration: single jacketed with heat-exchanger  
Max. arbetstemperatur: 80 °C  
Mobil tank: Nej  
Omrörare: Nej  
Total urtappning: Ja  
Uppvärmning/kylning: Ja  
Vätskeberörd yta: SS AISI 304 (V2A)  
Volym i liter: 2263

### Utrustning

Dokument finns: Nej  
Fläns för omrörare: Ja  
Märkskylt: Ja  
Teknisk ritning finns: Nej

### Översikt material

Material: Rostfritt 304

### Dimensioner av tank

Cylinderhöjd: 1.250 mm  
Invändig diameter: 1.433 mm  
Total höjd: 2.230 mm  
Ytterdiameter: 1.439 mm

**Tjocklek på tank**

Botten: 3 mm

Cylinder: 3 mm

Topp: 2,50 mm

**Mer**

Värmeväxlare: RVS 304

Isolerad: Nej