

2263 liter tank i Syrafast 316



186 000 SEK /st exkl moms

Additional information: 1 immersion sleeve for PT 100 probe inside the tank

Volumetric volume (L): 2.263 L

Pressure in tank: ATM - atmospheric

Max. temperature (°C): 120 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 16 L

Max Overpressure: 4 Bar

Max. working temperature: 120 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: yes

Position of manway: headside

Outlet of tank: DN50 DIN 11851

Top: 2,50 mm

Cylinder: 3 mm

Bottom: 3 mm

Internal diameter tank: 1.430 mm

Outer diameter tank: 1.640 mm

Cylinder height: 1.250 mm

Total height of tank: 2.330 mm

Empty weight tank: 750

SKU: 297576

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosfERIC

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 120 °C

Mobil tank: Nej

Övrig information: 1 immersion sleeve for PT 100 probe inside the tank; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2263

Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.250 mm

Invändig diameter: 1.430 mm

Total höjd: 2.330 mm

Ytterdiameter: 1.640 mm

Tjocklek på tank

Botten: 3 mm

Cylinder: 3 mm

Topp: 2,50 mm

Mer

Isolerad: Ja

Vikt: 750