227 liter tank i Rostfritt 304



244 000 SEK /st exkl moms

Additional information: pharmacy; 1 integrated control cabinet; the vessel was inspected and tested by the previous operator
Volumetric volume (L): 227 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 145 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 20 L
Max Overpressure: 5 Bar

Max onderdruk: 1 Bar
Max. working temperature: 145 °C
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: 35
Agitator: yes
Power: 0,37

Cylinder: 5,60 mm
Internal diameter tank: 600 mm
Outer diameter tank: 750 mm
Cylinder height: 615 mm
Total height of tank: 1.700 mm

Total outer width: 1.050 mm
Total outer length: 1.300 mm

SKU: 488460

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 145 °C
Mobil tank: Nej
Övrig information: pharmacy; we can’t give any guarantees about the heating/cooling jacket; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 3 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 227

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank
Cylinderhöjd: 615 mm
Invändig diameter: 600 mm
Total höjd: 1.700 mm
Ytterdiameter: 750 mm

Omrörare
Kraft (kW): 0,37

Tjocklek på tank
Cylinder: 5,60 mm

Mer
Isolerad: Ja