

2280 liter tank i Syrafast 316



202,000,00 kr /st exkl moms

Additional information: pharmacy; foot plates made of plastic; 1 heating connection cut off; suspension of the manhole cover incomplete; bump at the insulation jacket; pipe end cut flush

Volumetric volume (L): 2.280 L

Pressure in tank: pressure

Max. pressure (Bar): 3 Bar

Max. temperature (°C): 143 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 120 L

Max Overpressure: 4 Bar

Max. working temperature: 151 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 38

Agitator: yes

Number of revolutions: 1.460

Power: 15

Internal diameter tank: 1.400 mm

Outer diameter tank: 1.570 mm

Cylinder height: 1.100 mm

Total height of tank: 2.800 mm

SKU: 267712

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 143 °C

Mobil tank: Nej

Övrig information: pharmacy; foot plates made of plastic; 1 heating connection cut off; suspension of the manhole cover incomplete; bump at the insulation jacket; pipe end cut flush; we can't give any guarantees about

Övrig information2: the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2280

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.100 mm
Invändig diameter: 1.400 mm
Total höjd: 2.800 mm
Ytterdiameter: 1.570 mm

Omrörare

Kraft (kW): 15
Varvtal: 1.460

Mer

Värmeväxlare: RVS 304
Isolerad: Ja