

## 230 liter tank i Rostfritt 304



**95,000,00 kr /st exkl moms**

**Article type:** second-hand pressure tank

**Additional information:** we can't give any guarantees about the heating/cooling jacket

**Volumetric volume (L):** 230 L

**Pressure in tank:** pressure

**Material wet parts:** SS AISI 304L (V2A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Top type:** dished

**Shape of tank:** cylindrical

**Bottom type:** strong conical

**Bottom outlet:** yes

**Total discharge:** yes

**Fixation points:** 3 casters

**Type of HE on the cylinder:** dimple-jacket

**Position HE:** top side of the cylinder

**Heat exchanger:** RVS - 304 with rockwool insulation

**Insulation material:** Rockwool

**Outer jacket (ornamental wall):** RVS 304L

**Spray ball:** RVS 304L

**Valve:** RVS 304

**Gasket shut-off valve (mat):** unknown

**Suitable for food industry:** no

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** no

**Flange for agitator:** no

**CIP spray ball:** yes

**Tank outlet:** inside Ø 38 mm

**Total outlet valve:** yes

**Internal diameter tank:** 607 mm

**Distance from outlet to ground:** 195 mm

**Outer diameter tank:** 777 mm

**Cylinder height:** 750 mm

**Total height of tank:** 1.775 mm

**SKU:** 439361

## Mer information

### Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: strong conical

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304L (V2A)

Volym i liter: 230

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Tankutlopp: inside Ø 38 mm

Teknisk ritning finns: Nej

Utloppsventil: Ja

### Översikt material

Material: Rostfritt 304

Isoleringsmaterial: Rockwool

Ytterbeklädnad: RVS 304L

## **Dimensioner av tank**

Cylinderhöjd: 750 mm

Invändig diameter: 607 mm

Mått utlopp till marken: 195 mm

Total höjd: 1.775 mm

Ytterdiameter: 777 mm

## **Värmeväxlare**

Position värmeväxlare: top side of the cylinder

Typ av värmeväxlare på cylinder: dimple-jacket

## **Tjocklek på ytterbeklädnad och isolering**

Isoleringsmaterial: Rockwool

## **Mer**

Värmeväxlare: RVS – 304 with rockwool insulation

Isolerad: Ja