2355 liter tank i Syrafast 316



70 000 SEK /st exkl moms

Additional information: Pharmaceutical chemistry; Further technical documents available; Manhole cylinder DN 500 (this manhole has the manhole cover plated and the manhole cover screws are missing); one of the two tanks is approx. 50 mm lower in overall height due to shorter feet
Volumetric volume (L): 2.355 L
Pressure in tank: pressure and vacuum

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. pressure (Bar): 2 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Configuration: single-skin
Heat exchanger: no
Insulation: no

Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Outlet of tank: flange DN50
Top: 8 mm
Cylinder: 6 mm
Bottom: 6 mm

Internal diameter tank: 1.400 mm
Cylinder height: 1.140 mm
Total height of tank: 2.400 mm
Empty weight tank: 650

SKU: 438422

Mer information

Beskrivning av produkt

Material: Syrafast 316
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single-skin
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Pharmaceutical chemistry; Further technical documents available; Manhole cylinder DN 500 (this manhole has the manhole cover plated and the manhole cover screws are missing); one of the two tanks is
Övrig information2: approx. 50 mm lower in overall height due to shorter feet
Omrörare: Nej
Övertryck: 2 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 2355

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.140 mm
Invändig diameter: 1.400 mm
Total höjd: 2.400 mm

Tjocklek på tank
Botten: 6 mm
Cylinder: 6 mm
Topp: 8 mm

Mer
Isolerad: Nej
Vikt: 650