

2355 liter tank i Syrafast 316



94 000 SEK /st exkl moms

Additional information: Pharmaceutical chemistry; The drawing is a standard drawing; slight deviations are possible; 2 claws made of stainless steel 304; double jacket made of 1.4541 (stainless steel 304) around the lower cylinder area and the lower base

Volumetric volume (L): 2.355 L

Pressure in tank: vacuum

Max. pressure (Bar): 3,20 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 92 L

Max Overpressure: 2 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: flange DN50

Top: 7 mm

Cylinder: 6 mm

Bottom: 5,10 mm

Internal diameter tank: 1.400 mm

Outer diameter tank: 1.500 mm

Cylinder height: 1.138 mm

Total height of tank: 2.150 mm

SKU: 285415

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical chemistry ; The drawing is a standard drawing; slight deviations are possible; 2 support brackets, Aisi 304; Double jacket made of 1.4541 (Aisi 304) around the lower cylinder area and

Övrig information2: the lower bottom

Omrörare: Nej

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2355

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.138 mm
Invändig diameter: 1.400 mm
Total höjd: 2.150 mm
Ytterdiameter: 1.500 mm

Tjocklek på tank

Botten: 5,10 mm
Cylinder: 6 mm
Topp: 7 mm

Mer

Isolerad: Nej