2355 liter tank i Syrafast 316



95 000 SEK /st exkl moms

Additional information: Pharmaceutical chemistry; The drawing is a standard drawing; slight deviations are possible; 2 claws made of stainless steel 304; double jacket made of 1.4541 (stainless steel 304) around the lower cylinder area and the lower base
Volumetric volume (L): 2.355 L
Pressure in tank: pressure and vacuum

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. pressure (Bar): 3,20 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Volume: 92 L
Max Overpressure: 2 Bar

Max onderdruk: 1 Bar
Max. working temperature: 200 °C
Type HE on the bottom: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: flange DN50
Top: 7 mm

Cylinder: 6 mm
Bottom: 5,10 mm
Internal diameter tank: 1.400 mm
Outer diameter tank: 1.500 mm
Cylinder height: 1.138 mm

Total height of tank: 2.150 mm

SKU: 409439

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Pharmaceutical chemistry ; The drawing is a standard drawing; slight deviations are possible; 2 support brackets, Aisi 304; Double jacket made of 1.4541 (Aisi 304) around the lower cylinder area and
Övrig information2: the lower bottom
Omrörare: Nej
Övertryck: 3,20 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 2355

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.138 mm
Invändig diameter: 1.400 mm
Total höjd: 2.150 mm
Ytterdiameter: 1.500 mm

Tjocklek på tank

Botten: 5,10 mm
Cylinder: 6 mm
Topp: 7 mm

Mer

Isolerad: Nej