

2400 liter tank i Syrafast 316



228,000,00 kr /st exkl moms

Additional information: Pharmacy; Tank is equipped with 3 load cells (no guarantee of functionality)

Volumetric volume (L): 2.400 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 140 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 130 L

Max Overpressure: 3 Bar

Max onderdruk: 1 Bar

Max. working temperature: 120 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 25

Agitator: yes

Number of revolutions: 263

Power: 1,50

Cylinder: 8 mm

Bottom: 7,10 mm

Internal diameter tank: 1.450 mm

Outer diameter tank: 1.506 mm

Cylinder height: 1.000 mm

Total height of tank: 2.350 mm

SKU: 285475

Mer information
