

2410 liter tank i Syrafast 316



163,000,00 kr /st exkl moms

Additional information: Chemistry

Volumetric volume (L): 2.410 L

Pressure in tank: ATM - atmosferic

Max. pressure (Bar): 0,49 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: no

Volume: 132 L

Max Overpressure: 10 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: available

Number of revolutions: 211

Power: 3,60

Internal diameter tank: 1.500 mm

Cylinder height: 1.260 mm

Total height of tank: 3.160 mm

SKU: 563623

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: chemistry; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 0,49 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2410

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316



Dimensioner av tank

Cylinderhöjd: 1.260 mm
Invändig diameter: 1.500 mm
Total höjd: 3.160 mm

Omrörare

Kraft (kW): 3,60
Varvtal: 211

Mer

Isolerad: Ja