

24100 liter tank i Rostfritt 304



302 000 SEK /st exkl moms

Additional information: chemistry; Technical documents of an identical tank available; for this tank the techn. documents may be obtained afterwards; 1 rectangular opening approx. 500 x 600 mm in the upper bottom

Volumetric volume (L): 24.100 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 180 L

Max Overpressure: 6 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 100

Agitator: yes

Number of revolutions: 120 - 476

Power: 30

Top: 10 mm

Cylinder: 10 mm

Bottom: 12 mm

Internal diameter tank: 3.200 mm

Cylinder height: 2.450 mm

Total height of tank: 6.050 mm

SKU: 270865

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: chemistry; Technical documents of an identical tank available; for this tank the techn. documents may be obtained afterwards; 1 rectangular opening approx. 500 x 600 mm in the upper bottom; we can't

Övrig information2: give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 24100

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 2.450 mm

Invändig diameter: 3.200 mm

Total höjd: 6.050 mm

Omrörare

Kraft (kW): 30

Varvtal: 120 - 476

Tjocklek på tank

Botten: 12 mm

Cylinder: 10 mm

Topp: 10 mm

Mer

Isolerad: Nej