

## 2420 liter tank i Syrafast 316



**230 000 SEK /st exkl moms**

**Additional information:** Pharmaceutical Chemistry; Manhole DN 350/450 (sight glass in manhole cover missing); support ring made of Fe; flanges partly made of Fe

**Volumetric volume (L):** 2.420 L

**Pressure in tank:** vacuum

**Max. pressure (Bar):** 3,20 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 100 L

**Max Overpressure:** 16 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 200 °C

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Type HE on the cylinder:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** 130

**Agitator:** yes

**Number of revolutions:** 235

**Power:** 4

**Top:** 7 mm

**Internal diameter tank:** 1.400 mm

**Cylinder height:** 1.180 mm

**Total height of tank:** 3.550 mm

**SKU:** 290514

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Pharmaceutical Chemistry ; Manhole DN 350/450 (sight glass in the manhole cover is missing); support ring, Fe; Flanges partly made of Fe; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3,20 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2420

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316

**Dimensioner av tank**

Cylinderhöjd: 1.180 mm  
Invändig diameter: 1.400 mm  
Total höjd: 3.550 mm

**Omrörare**

Kraft (kW): 4  
Varvtal: 235

**Tjocklek på tank**

Topp: 7 mm

**Mer**

Isolerad: Nej