24400 liter tank i Rostfritt 304



419 000 SEK /st exkl moms

Additional information: Heating/cooling surface: Subfloor approx. 3 m² - Cylinder approx. 20.9 m² (divided into 3 zones); suitable for foodstuffs
Volumetric volume (L): 24.400 L
Pressure in tank: pressure
Max. pressure (Bar): 3 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 3 Bar

Material wet parts: SS AISI 304 (V2A)
Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes

Mobile tank: no
Total discharge: yes
Volume: 61 L
Max Overpressure: 4 Bar
Max. working temperature: 40 °C

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: cylinder

Outlet of tank: DN50 DIN 11851
Top: 8 mm
Cylinder: 4 mm
Bottom: 8 mm
Internal diameter tank: 2.900 mm

Outer diameter tank: 3.100 mm
Cylinder height: 2.900 mm
Total height of tank: 5.115 mm
Empty weight tank: 4.700

SKU: 703046

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated
Mobil tank: Nej
Övrig information: Heating/cooling surface: Subfloor approx. 3 m² – Cylinder approx. 20.9 m² (divided into 3 zones); suitable for foodstuffs
Omrörare: Nej
Övertryck: 3 Bar
Total urtappning: Ja
Undertryck (vakuum): 3 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 24400

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 2.900 mm
Invändig diameter: 2.900 mm
Total höjd: 5.115 mm
Ytterdiameter: 3.100 mm

Tjocklek på tank

Botten: 8 mm
Cylinder: 4 mm
Topp: 8 mm

Mer

Isolerad: Ja
Vikt: 4.700