

24450 liter tank i Rostfritt 304 (dubbelmantlad)



211 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: API650, VLAREM II, previous product Nitric acid 68%

Volumetric volume (L): 24.450 L

Max. density P (kg/m³): 1.405

Pressure in tank: ATM - atmosferic

Design pressure (Bar): 0,13 Bar

Max. temperature (°C): 50 °C

Material wet parts: SS AISI 304L (V2A)

Model: vertical

Configuration: double jacket for leak detection (system for detection not included)

Heat exchanger: no

Insulation: no

double jacket for leak detection (system for detection not included): yes

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: flat

Total discharge: no

Outer jacket (ornamental wall): RVS 304L

Manway(s): RVS 304L

Suitable for food industry: no

Documents included: yes, optional

Technical drawing included: no

Registration plate on the tank: yes

Inspection of: VLAREM II

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 500 mm

Agitator: no, optional

Top: 5 mm

Cylinder: 5 mm

Bottom: 5 mm

Internal diameter tank: 2.800 mm

Outer diameter tank: 2.880 mm

Cylinder height: 4.000 mm

Total height of tank: 4.500 mm

Empty weight tank: 3.800

SKU: 412046

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Designtryck för tanken: 0,13 Bar

Konfiguration: double jacket for leak detection (system for detection not included)

Max. arbetstemperatur: 50 °C

Maximal densitet för produkten: 1405

Mobil tank: Nej

Övrig information: API650, VLAREM II, previous product Nitric acid 68%

Omrörare: Nej

Tankens form: cylindrical

Total urtappning: Nej

Typ av botten: flat

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304L (V2A)

Volym i liter: 24450

Utrustning

Fläns för omrörare: Nej

Märkskylt: Ja

med besiktning av: VLAREM II

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Ytterbeklädnad: RVS 304L



Dimensioner av tank

Cylinderhöjd: 4.000 mm
Invändig diameter: 2.800 mm
Total höjd: 4.500 mm
Ytterdiameter: 2.880 mm

Tjocklek på tank

Botten: 5 mm
Cylinder: 5 mm
Topp: 5 mm

Mer

Isolerad: Nej
Vikt: 3.800