

24500 liter tank i Rostfritt 304



364 000 SEK /st exkl moms

Additional information: Brewery; Total height estimated according to drawing; 1 manhole diameter 450 mm with connection diameter 70 mm at the end of the cone bottom; wall thickness of 1000 mm of cylinder height 4 mm

Volumetric volume (L): 24.500 L

Pressure in tank: pressure

Max. pressure (Bar): 2,50 Bar

Max. temperature (°C): 50 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: no

Volume: 113 L

Max Overpressure: 2 Bar

Max. working temperature: 70 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Top: 6 mm

Cylinder: 3,50 mm

Bottom: 4,50 mm

Internal diameter tank: 2.882 mm

Outer diameter tank: 3.084 mm

Cylinder height: 2.500 mm

Total height of tank: 6.000 mm

SKU: 474482

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 50 °C

Mobil tank: Nej

Övrig information: Brewery; Total height estimated according to drawing; 1 manhole diameter 450 mm with connection diameter 70 mm at the end of the cone bottom; wall thickness of 1000 mm of cylinder height 4 mm; we

Övrig information2: can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 2,50 Bar

Total urtappning: Nej

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 24500



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 2.500 mm
Invändig diameter: 2.882 mm
Total höjd: 6.000 mm
Ytterdiameter: 3.084 mm

Tjocklek på tank

Botten: 4,50 mm
Cylinder: 3,50 mm
Topp: 6 mm

Mer

Isolerad: Ja