

250 liter tank i Rostfritt 304



49,000,00 kr /st exkl moms

Article type: second-hand pressure tank

Additional information: Top lid is missing, a new lid = 650 €.

There are two connections provided with 2 inch internal thread for mounting 2 immersion resistors with an insertion length of 500mm, the immersion resistors themselves are not included.

Volumetric volume (L): 250 L

Pressure in tank: pressure

Design pressure (Bar): 5,20 Bar

Max. pressure (Bar): 3,50 Bar

Max. temperature (°C): 100 °C

Material wet parts: SS AISI 304L (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: dished

Total discharge: yes

Fixation points: on skirt

Type of HE on the cylinder: atmospheric double jacket

Type of HE on the bottom: atmospheric double jacket

Heat exchanger: RVS 304

Fixation point(s): RVS 304

Suitable for food industry: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 355 mm

Tank outlet: inside Ø 32 mm

Outlet type: bsp female

Agitator: no, optional

Internal diameter tank: 695 mm

Distance from outlet to ground: 400 mm

Outer diameter tank: 795 mm

Cylinder height: 560 mm

Total height of tank: 1.370 mm

Empty weight tank: 300

SKU: 61114

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure

Designtryck för tanken: 5,20 Bar

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 100 °C

Mobil tank: Nej

Övrig information: Top lid is missing, a new lid = 650 €. There are two connections provided with 2 inch internal thread for mounting 2 immersion resistors with an insertion length of 500mm, the immersion

Övrig information2: resistors themselves are not included.

Omrörare: Nej

Övertryck: 3,50 Bar

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: dished

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304L (V2A)

Volym i liter: 250

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Tankutlopp: inside Ø 32 mm
Teknisk ritning finns: Nej
Utloppstyp: bsp female

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304

Dimensioner av tank

Cylinderhöjd: 560 mm
Invändig diameter: 695 mm
Mått utlopp till marken: 400 mm
Total höjd: 1.370 mm
Ytterdiameter: 795 mm

Värmeväxlare

Typ av värmeväxlare på cylinder: atmosfertical double jacket
Typ av värmeväxlare på botten: atmosfertical double jacket

Mer

Värmeväxlare: RVS 304
Isolerad: Nej
Vikt: 300